

TDS – Techniwax 9265

Information

Product Description

Techniwax 9265 is formulated for applications where Low Melting Point Microcrystalline waxes are required.

Physical Properties

<u>Test</u>	<u>Method</u>	<u>Specification</u>	<u>Typical</u>
Congealing Point °C	ASTM D 938	65-70	65
Viscosity @ 100°C / cSt	ASTM D 445	15-18	16
Penetration@ 25°C / dmm	BS EN 1426	20-30	22
Colour	ASTM D1500	Max 1	<1

Statement

- Formulated from materials whose refining history is fully traceable.
- Does not contain or come into contact with any animal or GMO products at any stage of its manufacture
- Does not contain residual solvents as per guidelines CPMP/ICH283/95.
- Has not been tested on animals by ourselves or on our behalf.

The information and recommendations in this publication are, to the best of our knowledge, reliable. Users must make their own tests to determine the suitability of these products for their own particular purposes. The company makes no warranty of any kind, expressed or implied, including those of merchantability or fitness for a particular purpose, other than that the material conforms to its applicable current Standard Specifications.

Date Prepared: 13MAR15

Date Revised: 22JAN20

Version: 4.0

Regulatory Approvals ⁽¹⁾

Techniwax 9265 is approved for use in

- Cosmetics
 - EU 1223/2009
 - COLIPA Recommendation 14

- Direct Food Contact
 - EU 10/2011
 - FDA CFR 178.3710 / 172.886
 - E905

- Pharmaceutical Excipients
 - USP XXXI / NF 26: Microcrystalline Wax
 - Pharm Eur (for Hard Paraffin)

- Skin Care Products
- Hair Care Products

(1) *Detailed local regulatory information is available upon request*

The information and recommendations in this publication are, to the best of our knowledge, reliable. Users must make their own tests to determine the suitability of these products for their own particular purposes. The company makes no warranty of any kind, expressed or implied, including those of merchantability or fitness for a particular purpose, other than that the material conforms to its applicable current Standard Specifications.